

MEHANICKA SILINA NA REDUKTORITE -- 4RPVI4RPVS vo KW														
In	(min-1)		GOLEMINA NA REDUKTOROT											
	n1	n2	180	200	225	250	280	315	355	400	450	500	560	630
112	1500	13.4	8.3	13	19	27	36	56	79	107	150	225	320	440
	1000	8.93	5.5	9	12.8	18	24	37	53	72	100	150	220	295
	750	6.7	4.1	6.5	9.6	13.5	18	28	40	53	75	112	165	225
125	1500	12	7.9	11	17.1	23.5	33	48	71	96	135	210	290	400
	1000	8	5.2	7.5	11.5	15.5	22	32	47	64	90	140	190	265
	750	6	3.9	5.5	8.5	11.5	16.5	24	35	48	67	105	145	200
140	1500	10.7	7.2	10.2	15	21	30	43	62	86	123	185	255	355
	1000	7.14	4.8	6.8	10	14	20	29	41	57	82	123	170	235
	750	5.36	3.6	5.1	7.5	10	15	21.5	31	43	62	92	130	175
160	1500	9.37	6.6	9	13.3	18.5	25.5	39	56	73	107	165	225	315
	1000	6.25	4.3	6	8.8	12.5	17	25.5	37	48	72	112	152	210
	750	4.69	3.3	4.5	6.7	9.3	12.8	19	28	36	55	83	115	160
180	1500	8.33	5.7	8	12	17	23.5	34	49	64	95	145	200	280
	1000	5.56	3.8	5.2	8.1	11.5	15.5	23.5	33	43	65	96	135	185
	750	4.17	2.8	4	6	8.5	11.7	17	25	32	50	73	102	140
200	1500	7.5	5.1	7.1	10.7	14.5	20	30	45	59	85	135	185	255
	1000	5	3.4	4.8	7.1	9.8	13.5	20	30	40	57	90	124	170
	750	3.75	2.5	3.6	5.3	7.3	10.1	15	22.5	30	43	67	93	127
224	1500	6.7	4.5	6.4	9.6	13.1	18	27	41	53	75	118	165	225
	1000	4.46	3	4.2	6.4	8.7	12.2	17.5	27	36	50	78	112	150
	750	3.35	2.2	3.2	4.8	6.6	9.1	13.5	20	27	37	59	83	112
250	1500	6	4	5.5	8.5	11.7	16	24	36	48	66	106	148	200
	1000	4	2.6	3.7	5.6	7.8	10.7	15.5	24.5	32	44	71	98	135
	750	3	2	2.7	4.2	5.8	8	11.7	18	25	33	53	74	100
280	1500	5.36	3.5	5	7.7	10.2	14.5	21	32	43	60	93	128	180
	1000	3.57	2.3	3.3	5.1	6.8	9.5	14	21.5	29	40	62	86	122
	750	2.68	1.8	2.5	3.8	5.1	7.1	10.7	16	21	30	47	64	91
315	1500	4.76	3.2	4.2	6.8	9.2	12.8	20	29	40	53	83	116	160
	1000	3.17	2.1	2.9	4.6	6.1	8.5	13	19	27	36	56	77	107
	750	2.38	1.6	2.1	3.4	4.6	6.4	9.6	14.5	20	27	42	58	80
355	1500	4.23	2.6	3.8	6.1	8.3	11.2	16.5	25.5	34	47	75	105	141
	1000	2.82	1.8	2.5	4	5.5	7.5	11.1	17	23.5	32	50	70	94
	750	2.11	1.4	2	3	4.1	5.6	8.3	12.8	17	23.5	37	52	71
400	1500	3.75	2.3	3.3	5.3	7	10.1	15	22.5	30	43	66	90	125
	1000	2.5	1.6	2.2	3.6	4.7	6.7	10	15	20	29	44	60	83
	750	1.88	1.2	1.7	2.6	3.5	5.1	7.5	11.2	15	21.5	33	45	62
450	1500	3.33	2	2.7	4.7	6.3	8.5	12.8	19	27	38	59	83	112
	1000	2.22	1.4	1.9	3.1	4.1	5.7	8.5	12.8	17.5	25.5	40	56	75
	750	1.67	1.1	1.4	2.3	3.2	4.2	6.4	9.6	13.3	19	30	42	57
500	1500	3	1.7	2.3	4	5.5	7.7	11.2	17.2	23.5	34	54	75	103
	1000	2	1.2	1.6	2.6	3.7	5.1	7.5	11.5	15.7	23	36	50	68
	750	1.5	0.85	1.2	2	2.7	3.8	5.6	8.5	11.7	17	28	37	51
560	1500	2.68		2	3.4	4.9	6.7	10	15	20.5	29	45	64	86
	1000	1.79		1.4	2.2	3.3	4.5	6.7	10	14	20	30	43	58
	750	1.34		1.1	1.7	2.4	3.4	5	7.5	10.5	14.5	22	32	44
630	1500	2.38		1.7	3.2	4.2	5.7	8.5	12.5	18	25.5	41	56	78
	1000	1.59		1.2	2.1	2.9	3.8	5.6	8.2	12.3	17	28	37	52
	750	1.19		0.85	1.6	2.1	2.9	4.2	6.2	9	12.5	20	28	40

TERMICKA SILINA KW													
In	n1	180	200	225	250	280	315	355	400	450	500	560	630
Pq1(KW)-za reduktor bez ladienje													
112-630	1500	25	32	41	52	66	87	110	140	175	220	280	345
	1000	22.5	28.5	37	46	59	77	98	125	160	205	260	325
	750	21	26.5	34	43	54	71	90	115	150	185	230	300